

# Fiberglass Shelters



Fiberglass shelters provide the perfect solution for protecting chlorination and de-chlorination equipment from environmental elements, therefore enhancing the life of equipment.

Fiberglass Enclosures are corrosion resistant, weather proof, low-maintenance, and affordable.

Additionally, fiberglass enclosures can be used in many other applications such as chemical storage, cooling tower control rooms, waste water pumping stations, and in any other situation where you need to protect your investment from theft and the environment.

## STANDARD FEATURES:

- Fiberglass reinforced polyester skins with one inch isocyanurate foam insulating core
- White UV protective polyester gel coat inside and out
- 125amp, main lug, 8 branch circuit panel in a NEMA 3R plastic enclosure
- Pre-wired using 12 ga. wiring in U.L. listed nonmetallic flexible conduit
- Two Duplex outlets (115v)
- Interior vapor-resistant incandescent lamp
- Corrosion resistant fan (intake or exhaust) with screened fiberglass hood
- Fixed Aluminum ventilation louver
- External weatherproof switch for fan and light
- Stainless steel lockset, stainless steel piano hinge, door gasket
- Galvanized plated lifting eye(s)
- Spring cushioned crash stop on door
- Fiberglass awning above doorway
- Equipment mounting board laminated to interior wall

## OPTIONS:

- Window in door
- Heater with thermostat & dedicated outlet
- Panic Hardware
- Partitions
- Double doors

Affordable \* Low-Maintenance \* Corrosion Resistant  
Weather Proof \* Turn-key Packages

Brochure, Fiberglass Shelter, Pg 1 of 2, 7/2020

Water Treatment  
Professionals



## Standard Shelter Sizes

|               | Length     | Width      | Height | Door Size     | Fan Size | Weight   |
|---------------|------------|------------|--------|---------------|----------|----------|
| GTI-SH-2854   | 2 ft, 4 in | 4 ft, 6 in | 7 ft   | 40 in x 80 in | 206 CFM  | 400 lbs  |
| GTI-SH-4848   | 4 ft       | 4ft        | 7 ft   | 36 in x 80 in | 206 CFM  | 475 lbs  |
| GTI-SH-5472   | 4 ft, 6 in | 6 ft       | 7 ft   | 40 in x 80 in | 206 CFM  | 625 lbs  |
| GTI-SH-7272   | 6 ft       | 6 ft       | 7 ft   | 40 in x 80 in | 206 CFM  | 700 lbs  |
| GTI-SH-9672   | 8 ft       | 6 ft       | 7 ft   | 40 in x 80 in | 698 CFM  | 815 lbs  |
| GTI-SH-7296   | 6 ft       | 8 ft       | 7 ft   | 40 in x 80 in | 698 CFM  | 850 lbs  |
| GTI-SH-9696   | 8 ft       | 8 ft       | 7 ft   | 40 in x 80 in | 698 CFM  | 985 lbs  |
| GTI-SH-12096  | 10 ft      | 8 ft       | 7 ft   | 40 in x 80 in | 698 CFM  | 1125 lbs |
| GTI-SH-72120  | 6 ft       | 10 ft      | 7 ft   | 40 in x 80 in | 698 CFM  | 1110 lbs |
| GTI-SH-96120  | 8 ft       | 10 ft      | 7 ft   | 40 in x 80 in | 698 CFM  | 1125 lbs |
| GTI-SH-120120 | 10 ft      | 10 ft      | 7 ft   | 40 in x 80 in | 698 CFM  | 1490 lbs |
| GTI-SH-96144  | 8 ft       | 12 ft      | 8 ft   | 40 in x 80 in | 702 CFM  | 1525 lbs |
| GTI-SH-144144 | 12 ft      | 12 ft      | 8 ft   | 40 in x 80 in | 702 CFM  | 1700 lbs |



Final Assembly



Finished Shelter  
Wrapped & ready to ship



Shelter set up  
on site

Brochure, Fiberglass Shelter, Pg 2 of 2, 7/2020