www.globaltreat.com
info@globaltreat.com
281-370-3425

Emergency Actuator

Model #: GTI-EA-U

For Cylinder or Ton Containers

REMOTELY OPEN & CLOSE VALVE ON A CHLORINE OR SULFUR DIOXIDE CYLINDER OR TON CONTAINER



Capabilities:

- Motor, gears, & controls assembled as one unit
- Battery operated with electric motor that rotates the valve stem towards the open or closed position for alignment, tests, & remote operation
- Operational integral leak detection for automatic shutdown
- Remote close by leak detector, panic button or other digital signals such as PLC or computer
- Designed to mount without interfering with, or requiring yokes or additional adapters for dispensers or discharging hardware
- Eliminates the need for scrubbers in certain applications per the uniform Fire Code



Features:

Enclosure: NEMA 4X
Battery: Two 12/24-Volt SLA
Charger: 120/240 VAC Automatic
Indicator: Three digit .5" LED's
Inputs: Maximum of three
Outputs: Maximum of four
Remote: Wired power enclosure
Rotation: Programmable up to 360°
Materials: Fiberglass, stainless steel, steel, brass, & RF nylon
Actuator Weight: 11 lbs
Torque: 40 ft/lb
Compatibility: Chlorine Institute 110 and conforms to CI Publication

Water Treatment Professionals








Emergency Actuator
Accessories

Remote pushbutton for actuators.

- One dry contact that can be connected to LD terminals
- Mounting holes and cable entries are created by the installer
- Weight: 2 lbs
- Shipping Size: 7” x 7” x 7”



Control Panel

- If two or more actuators are connected to the control panel a Remote Battery Box will be included
- Enclosure includes a power light, input/output isolation relay, & panic button for operator interface
- Sized specifically for each installation, weight & size will depend on the system



U-Clip Retainer: Required for each actuator on ton containers

Spare Batter: 12 Volts 7AH

Spare Batter – 12 Volts 5AH



GlobalTreat INC
The Clear Choice

www.globaltreat.com
info@globaltreat.com
281-370-3425